

50 Ohm RF Coaxial Cables


ACCL (ALMR) 600

Construction


Inner conductor	Solid copper	Φ4.47 mm
Dielectric	Foam /Solid PE	Φ11.56 mm
Shield	Bonded aluminium foil	Φ11.71 mm
Outer conductor	Tinned copper braid	Φ12.50 mm
Sheath	PVC/PE	Φ14.99 mm

Electrical & Mechanical Characteristics

Impedance	50±3 Ohm
Nominal capacitance	76.8 pF/m
Velocity of propagation	87%
Insulation resistance	>5000 Mohm.Km
Inner conductor resistance	1.7 Ohm/Km
Outer conductor resistance	3.9 Ohm/Km
Operating temperature range	-40°C - +85 °C
Min.bending radius	75 mm



PVC/PE sheath
 Foamed/solid PE dielectric
 Solid copper inner conductor
 Bonded aluminium foil
 Tinned copper braid outer conductor



Attenuation

Frequency(MHz)	Attenuation (dB/100 m)	Max. Attenuation(dB/100ft)
30	1.4	0.4
50	1.8	0.5
150	3.2	1.0
220	3.9	1.2
450	5.6	1.7
900	8.2	2.5
1500	10.9	3.3
1800	12.1	3.7
2000	12.8	3.9
2500	14.5	4.4
3000	15.7	4.8
5800	23.8	7.3